# **Pro9541dn Specifications**





OKI takes graphic arts printing to a new level with the Pro9541dn, offering outstanding print quality, higher print speeds, lower total cost of ownership, complete media flexibility plus the unique option of printing with a fifth colour. You can now print on-demand, the full range of process colours, with the addition of white or clear gloss.

The Pro9541dn is fully compatible with EFI Fiery XF 5.0 server which enables advanced colour management, including spot and process colours, optimising colour depth and print quality.

## A first in digital LED printing - CMYK +1

The Pro9541dn is an affordable and unique high definition printer that enables you to not only print the full range of process colours but also offers white.

- Print in a full range of process CMYK colours
- Plus now add a spot colour white or clear
- Stunning vibrancy of colour on dark or transparent media

#### Stunning high definition colour

The Pro9541dn uses the combination of digital LED technology and our Multi-Level ProQ technology to produce the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output
- Fully compatible with EFI Fiery® XF for advanced colour management

#### Low total cost of ownership

The Pro9541dn combines a highly competitive capital cost and ultra-high capacity toners cartridges to deliver a considerably reduced total cost of ownership, essential where high coverage and quality is demanded.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges and drums
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage

#### Speed that you can rely upon

Offering the highest printing speeds on the market, the Pro9541dn delivers faster short run on-demand printing.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)

2GB RAM and 1.2GHz processor for rapid throughput

#### Media flexibility to beat all others

Beating the competition hands down when it comes to media flexibility, the Pro9541dn enables you to print in-house on a complete range of media.

- Widest paper handling from A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Duplex printing as standard
- Prints on a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility

A3/A4	~
Colour/Mono	~
Prints A6 to 1321mm, up to 360gsm	<b>~</b>
White or clear spot colour	~
4. 20	



#### Pro9541dn - Colour and Mono Printer

PRINTER		OPERATOR PANEL	
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono. White: up to 45ppm (simplex) Clear: 18ppm	LCD Display	10.9cm Colour Graphic LCD (480x272 dots)
Time to first print	8 seconds colour, 8 seconds mono	GENERAL FEATURES	
Warm up time	50 seconds or less from power on		Standard RAM: 2GB; Maximum RAM: 2GB
Processor speed	1.2GHz	Memory	Optional Hard Disk Drive: 160GB
INTERFACE AND SOFTWARE		Environment	Operating temperature/humidity: 10°C to 35°C (17°C to 27°C recommended) / 10% to 85% RH (50% to 70% RH recommended)
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T		Storage temperature/humidity: -10°C to 43°C, 10% to 90%RH
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF	Power supply	Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz
Network & protocols	Printing (v1.7), XPS, SIDM  All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: IPv4/v6, ICMP, ICMPv6, IGMP, IGMPv2, LPR, Port9100, IPP, IPPS, FIP, FIP over SSL, HTTP, HTTPS, TELNET, IPP, Auto IP, LLTD, BOOTP, DHCP, SNMPv1/v3, SNMP Trap, DNS, DDNS, UPPR, Bonjour, WINS, SSL/TLS, SMTP, SMTP over SSL, POP3, SNTP, ICDP, FLDP, ODNSP, WSDPrint, WSD-Discovery, Web JetAdmin, NetBIOS over TCP, EtherTalk	Power consumption	Typical: 1200W; Max: 1500W; Idle: 200W (average); Power Save: <26W; Deep Sleep: <4W; Off Mode: <0.5W
		Noise level	Operating: 57dB(A); Standby: 32dB(A) or less; Power save: Inaudible
		Dimensions (HxWxD)	640 x 699 x 625mm
		Weight <sup>4</sup>	110.8kg
		Duty Cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month
OS Compatibility¹	Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 7 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8 (32-bit & 64-bit); Mac OS9 / OS X 10.3.9 - 10.9	Warranty	3 years extended warranty upon registration within 30 days of purchase
		Product order number	Pro9541dnWT: 46220201WT (with White Spot Colour Kit <sup>5</sup> ) Pro9541dnCL: 46220201CL (with Clear Spot Colour Kit <sup>5</sup> )
Advanced networking	Sec, EAP-PEAP, EAP-TLS, Secure Erase <sup>3</sup> , Secure Print <sup>3</sup> , Secure Print Job Encryption <sup>3</sup> , Storage Devices entire Encryption <sup>3</sup> , Storage(HDD) Initialize (format) <sup>3</sup>	Accessories (Order Numbers)	
and security		2nd/3rd paper tray	45530703
		2nd/3rd paper tray with castor	45530903
Utility suite¹	Print Job Accounting <sup>2</sup> , Print Job Accounting Enterprise <sup>2</sup> , Print Job Accounting Client, PrintSuperVision.net <sup>2</sup> , Template Manager <sup>2</sup> , Color Correct, Color Swatch <sup>2</sup> , Configuration Tool, PS Gamma Adjuster, Profile Assistant (Mac Only), PDF Direct Print, EFI Fiery XF Server Option (External color management server)	High Capacity Feeder	45530803
		Hard Disk Drive	160GB: 44622302
		EFI Fiery XF 5.0	Contact OKI for more information
		Spot Colour Kit <sup>5</sup>	White: 45531313; Clear: 45531413
TYPEFACES		Consumables (Order Numbe	ers)
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bit- map fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts	Toner cartridge* (42,000 pages)	Cyan: 45536572; Magenta: 45536571; Yellow: 45536570
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes	Toner Cartridge* (51,000 pages)	Black: 45536573
PRINT QUALITY		Toner Cartridge (10,000 pages)	White: 45536459
PRINT QUALITY  Resolution	ProQ4800 Multi-level technology, 1200 x 1200dpi	Toner Cartridge (20,000 pages)	Clear: 45536460
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect	Image drums** (40,000 pages)	Cyan: 45103739; Magenta: 45103738; Yellow: 45103737; Black: 45103740
PAPER HANDLING	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets	Image drums** (20,000 pages)	White: 45103743 Clear: 45103744
Paper capacity Paper capacity	of 80gsm  Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm;	Transfer Belt (150,000 pages)	45531223
optional trays	High Capacity Feeder: 1,590 sheets of 80gsm	Fuser Unit	45531113
Maximum paper capacity	2,950 sheets of 80gsm	(150,000 pages)	
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6; Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), SRA4, A4, A5, A6, B4, B5, B6	Waste Toner Box (40,000 pages) 45531503  *Toner: Number of A4 pages @ ISO coverage. Printer shipped with toner for 24,000 pages CMY and 38,000 pages K @ ISO.	
Paper weight	Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm; Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm	**Drum: Average number of A4 pages printed.	
Duplex	Standard		
Paper output	610 sheets face down tray, 300 sheets face up tray		

<sup>1</sup>Check local OKI website for latest driver releases and OS compatibility; <sup>2</sup>Windows only; <sup>3</sup>HDD required; <sup>4</sup>Including all consumables; <sup>5</sup>White Spot colour kit: 1 x 10,000 page toner cartridge, 1 x 20,000 page image drum; Clear Spot Colour Kit: 1 x 10,000 page toner cartridge, 1 x 20,000 page image drum

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Media Information: Certain types of media may not provide optimal results under default conditions.

# 3 Year On-site Warranty



Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: http://warranty.oki.com.au (Australia) or http://warranty.oki.co.nz (New Zealand). Without registration, the standard 1 year warranty applies.

### OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia T 1800 800 140 www.oki.com.au

#### **OKI DATA NEW ZEALAND**

8 Antares Place, Rosedale Auckland 0632 New Zealand T 0800 654 669



